

CLADDING SYSTEM



FURRING CLADDING SYSTEM



Installation Guide

- Furring channels are vertically fixed and aligned at 400 / 600mm c.c. to the wall.
- The gypsum boards, cement boards or acoustic gypsum boards are longitudinally fixed with suitable fasteners to the furring channel at a distance of 250 mm c.c.
- All joints are taped, and jointing compound is applied. Cladding is finished smooth ready for painting.

Description

Furring cladding profiles are manufactured from roll formed hot dipped galvanized steel coils and are available in different size and thickness.. Our profiles can be assembled on all types of gypsum boards, cement boards & acoustical boards.


The profile are manufactured from materials that comply with ASTM C 653M. Our finished profiles comply with ASTM C 645.

Galvanization coating (standard G40 (Z120) as per ASTM C 645). Standard profiles are produced in 3 meter length. Other galvanization coating requirements or lengths can be supplied upon request on minimum ordering quantity.



The system includes furring channels, gypsum boards / cement boards / acoustic gypsum boards etc apart from the normal accessories like joint compound fillers, screws, nails etc.



Furring Cladding System



Item No.	Description
1.	Furring Channel (FC 35 / FC 50)
2.	Gypsum / Cement Board / Gypboard Acoustic
3.	Dry Wall Screws
4.	Fiber Tape
5.	Fisher



Profiles	Length (MM)	Reference	Dimension (MM)	Thickness (MM)	
				Standard	Special Order
Furring Channel	3000	FC 35	70 X 22	0.45	0.50 - 0.90
		FC 50	85 X 22	-	0.45 - 0.90

FURRING CLADDING SYSTEM



FURRING CLADDING SYSTEM



Metal Product Company's quality system for production and development is
ISO 9001, 14001, 45001 Certified.



Metal Product Company many years of experience of the optimal utilization of our
steel production system. We place this know how at the disposal of the building
trade both through our printed information materials and personal advice
given to the major projects



P. O. Box 3973, Safat 13040, State of Kuwait, Tel.: +965 2473 1287 / 2473 1291 / 2473 7916, Fax: +965 2473 7932

Email: sales@mpckw.com / info@mpckw.com

www.mpckw.com